Roman Blind Headrail



1.21

States in its

. .

Roman Blind Headrail

Made to Measure Headrail:

- Strong 1.2-gauge profile.
- Cords adjustable in 1 click with no screws.
- Transit locking pin.
- Child safety components included.
- 5 Year warranty.
- Breakaway gear drives at no extra cost.

Choice of 3 different gear drives:

1:1 with Integrated Breakaway

3.5KG Weight limit. This is a quick operation gear drive.

If breakaway cog is released it can be placed back into the gear housing very easily. Chain must be at least 60cm from floor.

IMPROVED 1:4 with Integrated Breakaway

10KG Weight limit. This is a slower but smoother gear drive. If breakaway cog is released it can be placed back into the gear housing very easily. Chain must be at least 60cm from floor.

1:4 NON-Breakaway

7.5KG Weight limit. Non-Breakaway chain cog,

Chain must be at least 150cm from floor, secured with chain retainer (provided)

0	utain		Date			
		Pennikook Hood Funtar	Account Name			
Ral			Order Referens			
5	upples de Suppler	1.0392.20409 n° 0392.400964 udro@curtaincaliupples.com www.curtaincaliupples.co.uk	Delivery Addre (if different to account addres			
RS Easylock Roma	Track Size	Form	Chain or Blind	Gearing (1:1 Breakaway)	RH or LH	Colour of Chain
Here reference	mark size	Height	Drop (Please Specify which)	(1:4 Breakaway) or (1:4 NON Breakaway)	Operation	constr of chain

Order form available on request, or you can download form our website www.curtainrailsupplies.com

Roman Blind Headrail

Made to Measure Prices:

Size Up to:

60cm 80cm 100cm 120cm 150cm 175cm 200cm 225cm 250cm 275cm 300cm 325cm 350cm



Minimum blind size is 37cm

Headrail comes complete with shaped plastic bottom bar and universal brackets. Extra cord spools available at no extra cost, if requested at time of ordering

Choice of chain colours at no extra cost: Chrome (non-rust) as standard.



Antique Brass Chrome (chrome plated brass that will not rust) Copper Brass Grey Nickel White Plastic is also available

Roman Blind Child Safety

Our Roman Blind Systems are tested to British Standards BS EN 13120:2009 +A1:2014.

Operating Chains & Cords with NO Breakaway:

The important point of calculation is the installation height of the blind or track, this determines how long the chain or cord can be. The bottom loop of the chain or cord must be at least 150cms from the floor and secured with a safety device, without the safety device the product is not compliant and should not be fitted. Example – Headrail installation height 200cm, chain/cord length will be 50cms maximum.

OR

Operating Chains with Breakaway:

If the operating chain/cord has a breakaway device then the bottom loop of the cord/chain can be 60cms from the floor and a chain retainer is not required. This applies to our 1:1 and 1:4 Integrated Breakaway Roman Blinds.



Roman Blind Child Safety

Accessible Inner Cords (Roman Blind Pull Cords at the rear)

The maximum distance between two consecutive attachment/retention points *(normally rods, pockets or blind rings)* shall be less than or equal to 20cms. Any of the traditional methods of fixing the cord to the bottom rod pocket can be used if the rods are no more than 20cms apart in all areas of the Roman blind.

For Roman Blinds with rod pockets greater than 20cms at any point a Curtain Rail Supplies Ltd breakaway device must be used on each cord. The device that we supply with our Roman Blinds is the Safety Cord Toggle. The cord should be left unknotted to ensure that the cord can pass through. This must be secured to the blind to ensure that this doesn't fall to the floor and become a choking hazard in the event of a breakaway happening *(stitched or using cable tie).*

These toggles are supplied with every Curtain Rail Supplies Ltd Roman Blind at no extra cost.



Using Additional Cord Breakaway Devices

To prevent cords being pulled up into the headrail, additional devices are available. On a minimum of the bottom two rod pockets, Cord Breakaway Devices can be used. This enables you to tie a knot to the cord underneath the Safety Cord Toggle, the knot also ensures the Toggle cannot fall to the floor.



Cord Breakaway Device For Pockets or Eyelets

A two-part Safety device for use and tested with Curtain Rail Supplies Roman Blinds. Releases under 6KG. (Packet of 100)



Cord Breakaway Device For Roman Blind Tape

A two-part Safety device for use and tested with Curtain Rail Supplies Roman Blinds. Releases under 6KG. (Packet of 100)

E: sales@curtainrailsupplies.com

CRS Battery Operated Roman

MOTORISATION MADE AFFORDABLE

- Fully Tested 6KG Load Weight.
- Battery Life tested on 500 lift / lower operations.
- Supplied with a Lithium Battery.
- Easy step by step pairing and limit setting.
- Minimum blind size is 47cm.
- Sleek modern handset with magnetic wall bracket.
- 5 Year Warranty.

Made to Measure Prices:

Size Up to:	Trade Price
60cm	
80cm	
100cm	
120cm	
150cm	
175cm	
200cm	
225cm	

Prices includes Lithium battery: Battery

must have an initial 16 hours charge.

Accessories:

Single Channel Remote 15 Channel Remote Charger for Battery





Roman Blind Accessories



Clear Clip on ring for 4mm Fibreglass Rod (Pack of 100)



Clear Blind Ring 7mm inside / 13mm outside diameter (Pack of 1000)



Brass Ring 9mm inside / 13mm Outside Diameter (Pack of 200)



Blind Cord Heavy Duty 1.3mm thickness (500m Roll)



Chain Stop (Supplied as standard on 1:1 gear drive) (Pack of 100)



5mm Nickel Eyelets (Pack of 1000)

Roman Accessories

Fibreglass Rods

4mm Diameter

75cm Length (pack of 25 price)
100cm Length (pack of 25 price)
150cm Length (pack of 25 price)
200cm Length (pack of 25 price)
400cm Length (Pack of 10 Price)
400cm Length (Pack of 100 Price)

(Pack of 100) (Pack of 100) (Pack of 100) (Pack of 100)

8mm Diameter

500cm Length (Pack of 5 Price) 500cm Length (Pack of 100 Price)

Fibreglass Rod Endcaps 4mm only (Pack of 250)

Wood Rod 240cm 6mm Diameter

(Pack of 10) (Pack of 100)

9mm Diameter

(Pack of 10) (Pack of 100)

Bottom Bar Hardened PVC Oval bottom bar 400cm length, 25mm width, 9mm depth (Included in our made to measure Roman Blinds)

(Pack of 5)

(Pack of 50)





